



 <p>OBDCheck VP11</p> <p>Version: V3.20210628</p> <p>User Manual Bedienungsanleitung</p> <p>Language: English, Deutsche</p>	 <p>Scan the QR code or visit www.veepeak.com to get the latest FAQ & troubleshooting, user manual and customer support.</p>	<p>Content</p> <ul style="list-style-type: none"> 1. Compatible Vehicles2 2. Product Specifications3 3. Setup Instructions3 4. Compatible Apps4 5. FAQs and Troubleshooting5 6. Support and Warranty9 7. Disclaimer10 <p>Benutzerhandbuch</p> <p>Deutsche Bedienungsanleitung11</p> <ul style="list-style-type: none"> 1. Installationskurzanleitung12 2. Unterstützte Fahrzeuge13 3. Kompatible Geräte13 4. Support und Garantie14 	<p>The Veepeak OBDCheck VP11 is an easy-to-use, inexpensive and small OBD2 device that turns your Bluetooth-enabled Android or Windows smartphone or tablet into a sophisticated diagnostic scan tool and real-time parameter monitor. Read and clear trouble codes, reset Check Engine light as well as display live sensor readings with the use of a downloaded OBD2 App such as Torque. The adapter works on OBD II compliant vehicles and is a very useful little gadget that will save you time and money.</p> <p>Note</p> <ul style="list-style-type: none"> • It's recommended that you unplug the device if it will not be used for some time (on cars with old batteries, the time should be shorter). • Do not have any operations on the app while driving. Always focus on driving. • Simply erasing the trouble code does not 	<p>mean the fault have been solved. You should repair your vehicle as soon as possible.</p> <ul style="list-style-type: none"> • Not all trouble codes can be read as OBD2 is primarily designed for engine diagnostics system. Other systems like ABS, SRS, VSC, TPMS etc. use different protocols to communicate so check the app capabilities. Generally what you can do with the device depends on what features the app provides. <p>1. Compatible Vehicles (OBD-II or EOBD) (Cars and light trucks made since the following year): US: 1996, Canada: 1998, Mexico: 2006, Australia: 2006 (gas), 2007 (diesel) Brazil: 2007 (gas) European Union & UK: 2001 (gas), 2004(diesel)</p>	<p>India: 2010 Mexico: 2006, etc.</p> <p>2. Product Specifications</p> <ul style="list-style-type: none"> 1. Communication method: Bluetooth 2. Supported Devices: Android phone & tablet, Windows phone, tablet & pc 3. Operating voltage: 9V~16V 4. Operating current: 25mA 5. Working temperature: -40~85°C 6. Dimension: 1.89 x 1.26 x 0.98 inches 7. Supported OBD II Protocols: SAE J1850 PWM, SAE J1850 VPW, ISO 9141-2, ISO14230-4 (KWP2000), and ISO15765-4 CAN <p>3. Setup Instructions</p> <p>Step 1: Download and install the APP at your choice onto your phone (see compatible app list in Part IV).</p>	<p>Step 2: Plug the adapter into the OBD II port on your vehicle. Make sure it fits well. (Red LED On)</p> <p>Step 3: Turn ignition key to the ON position (or start the engine).</p> <p>For Push Button Start vehicles, press the button once to twice without putting your foot on the brake pedal (check your car manual).</p> <p>Step 4: Enable Bluetooth on your phone and pair with "OBDDII" (You may need to wait for a few seconds for "OBDDII" to show up; PIN is 1234).</p> <p>Step 5: Run the APP, make any necessary connection settings and connect.</p> <p>4. Compatible Apps (may require separate purchase) and Settings</p> <p>Android: Torque Lite/Pro, OBD Fusion, DashCommand, Car Scanner ELM OBD2, OBD Auto Doctor, Dr Prius, Piston and other ELM327 compatible Apps</p>	<p>Windows: OBD Auto Doctor, EOBD Facile, Car Scanner, etc.</p> <p>Torque: Setting>OBD2 Adapter Setting> Connection Type: Bluetooth; Choose Bluetooth Device: OBDDII. Quit and restart Torque.</p> <p>DashCommand: Settings>OBD-II Interface Type: Select "ELM"</p> <p>Other Apps have similar settings. If you are not sure, contact us.</p> <p>5. FAQs and Troubleshooting</p> <p>1) Is an app required? An OBD2 app is required to work with the adapter and the functions you can get mainly depend on the app you use. It requires download from Google Play Store and some may need separate purchase.</p> <p>2) Does it work with iOS devices? Or Android head units?</p>	<p>Unfortunately the VP11 does not work with iOS due to Apple's limitation. You should choose the Bluetooth LE (4.0) model for iOS. The Vp11 may have compatibility issue with some Android head units and we do not have a support list due to the complexity of the market.</p> <p>3) Could not pair with "OBDDII" Turn off & on Bluetooth; restart your phone and try again. When OBDDII shows as paired, connected, or previously connected, you can start the app to connect.</p> <p>4) Can I leave the adapter plugged in all the time? You can leave the adapter plugged in all the time if your car battery is not too old. If you leave your car sitting for more than 1 week, we recommend that you remove the adapter.</p> <p>5) "OBDDII" is not showing up on my phone's</p>
--	--	--	---	--	---	---	---	---

<p>Bluetooth device list. First check if the red light is on. If not, check if the cigar fuse of your vehicle is in good condition. You can also try with another vehicle to verify.</p> <p>6) App not connecting to OBD-II adapter. Make sure the app is compatible, "OBDDII" is paired with your phone and you have made the required App connection setting.</p> <p>7) Cannot connect to vehicle/ECU. Verify if your vehicle is OBD2 compliant. Make sure the ignition key is ON or start the vehicle to try. Then try it on another vehicle.</p> <p>8) Can it reset my ABS, airbag, and other non-Check Engine lights? Most OBD2 Apps only provide basic check engine light diagnostics. You will need a specific App that can do diagnostic on these modules</p>	<p>on your specific vehicle. Contact us or the app developer if you are not sure. It cannot reset oil change or maintenance required lights.</p> <p>9) Which sensor data can I get? Readable parameters depend on what's installed on the OBDDII system by the manufacturer. Generally, newer vehicles will give more readings and faster refresh speed. Some parameters like transmission temp are manufacturer-specific and you will need to add custom PID.</p> <p>10) The adapter does not fit into the recessed area of the OBD port or is hard to plug in and out. Use our OBD2 extension cable (search for Veepeak OBD2 extension cable on amazon)</p> <p>If you could not find the answer or have troubles getting the device to work, please</p>	<p>feel free to reach out to us for assistance.</p> <p>6. Support and Warranty For technical support or warranty service, please contact us via one of the following ways: • Phone: +1 (833) 303-1434, 9:00AM - 5:00PM CST, Monday – Friday • Email: support@veepeak.com • Visit www.veepeak.com to submit a contact form. Please describe your issue in as many details as possible and include a screenshot if you get any error message. Emails usually be answered within 24 hours. Products are covered by one-year hassle-free replacement warranty against defect.</p>	<p>7. Disclaimer Features and functions are offered and achieved through third-party Apps. Product names, logos, brands, vehicle makes/models and other trademarks featured or referred to within this user manual are the property of their respective trademark holders. Use of them does not imply any affiliation with or endorsement by them.</p>  <p>Scan the QR code or visit www.veepeak.com to get the latest FAQ & troubleshooting, product registration and customer support.</p>	 <p>OBDCheck VP11</p> <p>Bedienungsanleitung</p>	<p>1. Installationskurzanleitung</p> <ol style="list-style-type: none"> 1. Laden Sie sich eine entsprechende App herunter und installieren sie auf Ihrem Smartphone. Empfohlene Apps (Einige sind kostenpflichtig): Car Scanner ELM OBD2, Torque Lite (oder paid Pro version), OBD Fusion, DashCommand, EOBD Facile, Dr Prius. 2. Stecken Sie den Adapter in den Steckplatz Ihres Fahrzeuges. Somit sollte die rote Power-LED leuchten. 3. Schalten Sie die Zündung und ggf. den Motor an. 4. Aktivieren Sie die Bluetooth-Funktion Ihres Smartphones und wählen Sie das Gerät „OBDDII“ aus, geben Sie den Code 1234 ein. 5. Wenn OBD II gekoppelt ist (Es wird „paired, connected, or previously connected“ angezeigt), starten Sie die App und nehmen Sie folgende 	<p>Einstellung vor: CAR SCANNER ELM OBD2: Setting > Connection > Connection type: Bluetooth; Device name: OBDDII. Torque: Setting > OBD2 Adapter Setting > Connection Type: Bluetooth; Choose Bluetooth Device: OBDDII. DashCommand: Settings > OBD-II Interface Type: Select „ELM“.</p> <p>2. Unterstützte Fahrzeuge (Baujahr) US: 1996 GB and EU: 2001 (Benzin), 2004 (diesel) Australia – 2006 (Benzin), 2007 (diesel)</p> <p>3. Kompatible Geräte Android Smartphone/Tablet, Bluetooth-fähiges Windows PC; Es ist nicht mit iOS kompatibel; Android Kopfhörers sind nicht zu empfehlen.</p>	<p>4. Support und Garantie Email an support@veepeak.com. Emails werden binnen 24 Stunden beantwortet. Besuchen www.veepeak.com oder scannen die QR code für FAQs und Lösungen. Die Garantiezeit beträgt 1 Jahr.</p>  <p>Scannen Sie den QR-Code, um Produktinformationen, Benutzerhandbuch und Kundensupport zu erhalten. Oder besuchen Sie www.veepeak.com.</p>
---	--	---	--	---	--	---	--